


- Notes:
1. 100% open & short with miswire testing
 2. Test Conditions:
 - 1). Conductive Resistance: 5Ω Max
 - 2). Short Open Determinant: 20kΩ
 - 3). Insulation Resistance: 5mΩ Min at DC300V

15	Braid Net Tube Black (3) OD:10mm L=495mm	1pcs
14	Acetate Tape Black 50*20mm*2, 40*10mm	2pcs
13	Acetate Tape Black 110*15mm	1pcs
12	SAS 68P Housing: ABS, Black	1pcs
11	HD Mini-SAS Housing: PBT, Black	1pcs
10	Overmold: PVC 45P Black	5G
9	Premolding: LDPE Nature	10G
8	Connector: SATA 15P/M G/F Black	1pcs
7	Connector: SAS 68P/F 15U" Black	1pcs
6	PCB: SAS 68P Double Layout	1pcs
5	PCB: HD Mini-SAS 18P Double Layout Green*1;Blue*1	2pcs
4	UL1007 24AWG TS OD: 1.4mm Black*1;Orange*1;L-75mm	2pcs
3	UL1007 22AWG TS OD: 1.6mm Black*1;Red*1;Yellow*1;L=75mm	3pcs
2	30AWG*4 Ø3.2*0.8mm (Red, White, Green, Black)+30AWG*1 Ø0.8mm Black L=520mm	2pcs
1	30AWG*2C+Drain+AL+Mylar Ø2.1*0.9mm Blue 12G Cable L=520mm	8pcs

Part #	SAS68-SASM36-20	Part #		Cable Length
Title	20 inch U.2 (SFF-8639) to HD Mini-SAS (SFF-8643) Cable with SATA Power 15-Pin	SAS68-SASM36-20		20 inch
Unit	 PI Manufacturing Corp.			
mm				

RoHS